

### THE WOOD

Turada<sup>®</sup> Hardwood Shingles are manufactured by Superior Shingles and Wood Products (SSWP) in Guyana, South America. They are produced from sustainably harvested Wallaba logs. Wallaba is the most abundant timber species growing on the "White Sands Forest Belt" that stretches midway across the three Guianas (Guyana, Suriname, and French Guiana). SSWP uses logs which are over 24" in diameter, thereby ensuring that only mature Wallaba trees are felled. Young Wallaba trees remain in the forest, guaranteeing species availability in future generations.



Turada<sup>®</sup> Wallaba is a durable and attractive hardwood. It is significantly stronger than traditional red cedar or treated pine shingles. Turada<sup>®</sup> brand shingles are easy to handle and easy to install. Turada<sup>®</sup> Hardwood Shingles:

Are naturally resistant to insects and decay Have withstood category 5 hurricane winds Are the highest fire-rated wood shingle Have a lifespan of over 50 years

### **GLOBAL DEMAND**

Turada® Hardwood Shingles are highly valued, specified by architects worldwide, and distributed globally. Examples of projects that have used Turada® Hardwood Shingles include prestigious resorts, hotels, and villas in various countries such as Australia, South Africa, Mauritius, the Polynesian Islands, the Middle East, the United States and throughout the Caribbean.



## **ENVIRONMENTAL**

Turada® Hardwood shingles do not require chemical treatment, which makes them an environmentally responsible green building product. They also weather over time to a beautiful silver-gray color which results in a reflective, cool roof. This helps reduce environmental heating and lowers cooling costs.



### THE FACTORY

SSWP's modern shingle plant assures production that meets the highest standards of quality in the industry. This state-of-the-art facility has been in operation since 2001 and has the capacity to produce approximately 200,000 square feet of shingles per month.

### SHINGLE DESCRIPTION

Length: 18"

Width: 3" to 9" (average 6") Butt Thickness: 5/2-1/4"

(If you need different specifications, please contact us)



# FOR MORE INFORMATION AND TO CONTACT US:

superiorshingle.com

**VIRTUAL** 

CEO - howard@bulkantimbers.com Factory Manager - george@bulkantimbers.com US Sales - info@turadashingles.com

TELEPHONE

Office: (+592) 261.3384 Fax: (+592) 261.3392 Manager: (+592) 688.4606

MAILING 65 Bel Air Estate Greater Georgetown Guyana, S.A.